


## Ref. 2482 VISION 5 VIDEO DISTRIBUTOR



### DESCRIPCIÓN

Video Distributor of spare parts for inclusion or replacement in VISION 5 installations.

Video distribution in several outputs.

Must be used in all video signal bifurcations.

Video distributor includes two diagnose led. Any led will be turned on when its matched output is enabled (displaying that video signal is present in the monitor plugged in this output).

Small size allows installation in electrical cabinets. Can be flush-fit in standard boxes 10x10 cm. With adhesive strips for fixing, or may be screwed directly onto the wall.

**VISION 5 System:** Simplified installation video (only B/W) door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

The technology "differential video" employed allows to transmit the video signal with the highest quality without coaxial cable. The equipment related with the video signal should be VISION 5 for these installations without coax cable.

Communication is private.

In new works, lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity is 40 apartments (1 monitor per apartment) and up to 50 metres or 8 floors in the block. The monitor of the apartment needs a battery that supplies the necessary power.

### TECHNICAL SPECIFICATIONS

Balanced differential video signal.

Power supply tension: 18 Vdc + 4%

Maximum consumption: 15 mA

Operating temperature: 0-60° C

Dimensions: 62x70x20 mm (height-width-depth).